

SEACOMAIR 265CFS Compressor stationary



Meets all international breathing air standards for Grade "E" Air DIN EN12021



**High pressure breathing air Compressor, fully automatic.
Charging rate 265 l/min. (9 cfm) Extremely compact size for Dive Centers,
Marine and Industrial applications!**

Standard Features

- Electric 5,5 kW 400Volt, three phase 50Hz
- Durable powder coated, compact cabinet for stationary operation
- Cabinet colors black or blue
- Main control panel
- Pressure maintaining valve
- Pressure relief valves at all stages
- Fully automatic condensate drain
- Final pressure switch with gauge
- Hour meter
- Final pressure gauge 400bar / 5800psi
- External oil level sight glass indicator with oil drain
- Two-chem breathing air purification system with activated carbon/molecular sieve
- Refill Time: 10 Liter (70cu.ft.) cylinder in app. 8 min
- Two (2) high pressure filling hoses with on/off valve and bleed for SCUBA (INT or DIN 200/300)
- One year warranty
- Noise: 75 dB (ISO3746)
- Weight: 155 Kg (341 lbs)
- Dimensions: L 35"(90) x D 24"(60) x H 33,5"(85 cm)

Specifications

- Construction: Continuous duty air cooled, three stage, three cylinder high pressure compressor, all stainless steel interstage and final stage coolers Mounted in a powder coated steel cabinet.
- Max Pressure: 220bar/3200psi or 330bar/4700psi (Option)
- Approx.Outup: 265 l/min / 9 cfm / 16 m³/h
- Max R.P.M.: 1550
- Lubrication: Splash lubrication with oil thrower pin
- Oil Type: SeaComAir synthetic compressor oil
- Oil Capacity: 1,5 Liters (51 oz.)
- Drive motors: AC el. motors 400Volt, three phase 50Hz o.60Hz
- Features: Automatic condensate drain system with collector
Final pressure switch with gauge and automatic shut-off
Hour meter

Factory Options

- MP330: Compressor 300bar/4300psi pressure
- PS300/CFS: Pressure Switch 300-200bar(4300/3000psi)
- PG2010: Interstage Pressure Gauges (3 pcs)
- LO2015: Low oil shut down switch
- FPE4FV: Filling Panel Econo, Four Outlets

Type

Model	Description	Charging Rate	Drive Motor
SCA265E43/CFS	Compressor 265 l/min 220bar	265 l/min/ 9 cfm/ 16 m ³ /h	5,5kW Electric 400V/50Hzo.60Hz 3Ph



www.seacomair.com

© SeaComAir 2009 SCA265V/CFS

SeaComAir Germany
Grenzhub 5a • D - 83229 Aschau
Tel. +49/(0)8057/904674 • Fax +49/(0)8057/904676
e-mail: info@seacomair.com

Price and Specification are subject to change without notice. All pricing EX-Works, plus shipping, insurance and documentation.

SEACOMAIR 265 Vertikus Compressor



Meets all international breathing air standards for Grade "E" Air DIN EN12021



**High pressure breathing air Compressor, Charging rate 265 l/min. (9 cfm)
Compact small size for Fire Departments, Marine, Dive Centers and Industrial applications!**

Standard Features

- Electric 5,5 kW 400Volt, three phase 50Hz or 60Hz
- Durable powder coated, compact cabinet for stationary operation
- Pressure maintaining valve
- Pressure relief valves at all stages
- Manual condensate drain
- Purification Cartridge Holder easy to maintain
- Final pressure gauge 400bar / 5800psi
- Two-chem breathing air purification system with activated carbon/molecular sieve
- Refill Time: 10 Liter (70cu.ft.) cylinder in app. 8 min from 0-3000 psi/200 bar
- One high pressure filling hoses with on/off valve and bleed for SCUBA (INT or DIN 200/300)
- One year warranty
- Noise: 82 dB (ISO3746)
- Weight: 126 Kg (277 lbs)
- Dimensions: L 24" (60) x D 20" (50) x H 38" (98 cm)

Specifications

Construction: Continuous duty air cooled, three stage, three cylinder high pressure compressor, all stainless steel interstage and final stage coolers Mounted in a powder coated steel cabinet.
 Max Pressure: 220bar/3200psi or 330bar/4700psi (option)
 Approx.Outup: 265 l/min / 9 cfm / 16 m³/h charging rate
 Max R.P.M.: 1550
 Lubrication: Splash lubrication with oil thrower pin
 Oil Type: SeaComAir synthetic compressor oil
 Oil Capacity: 1,5 Liters (51 oz.)
 Drive motors: AC electric motors 400Volt, 3 phase 50Hz o.60Hz

Factory Options

- MP330: Compressor 300bar/4300psi pressure
- HMAE100: Hour meter Analog
- ASP100: Auto Stop/Shut Off pressure switch
- PS300/100: Pressure Switch 300-200bar(4300/3000psi)
- ACD100: Automatic condensate drain
- PG2010: Interstage Pressure Gauges (3 pcs)
- LO2015: Low oil shut down switch
- FPE4FV: Filling Panel Econo, Four Outlets

Type

Model	Description	Charging Rate	Drive Motor
SCA265E43/VERTIKUS	Compressor 265 l/min 220 bar	265 l/min/9 cfm/16 m ³ /h	5,5kW Electric 400V/50 o.60Hz 3Ph



www.seacomair.com

SeaComAir Germany
 Grenzhub 5a • D - 83229 Aschau
 Tel. +49/(0)8057/904674 • Fax +49/(0)8057/904676
 e-mail: info@seacomair.com