

SEACOMAIR 265E43/CFSF3 Electric 340 bar/5000 psi



Meets all international breathing air standards for Grade "E" Air DIN EN12021

ISO9001: 2009 Certified Factory



Two Filling Valves DIN200 or DIN300 with On/Off Valve and bleed



High pressure breathing air Compressor, fully automatic. Charging rate 315 l/min. (13 scfm) Extremely compact size for Marine, Police, Military and Industrial applications!*

Standard Features

- **Charging rate* 315 l/min / 14 scfm @ 340bar/5000psi**
- Fills an 11 Liter (80cu.ft.) cylinder in app. 5,5 min.*
- Durable powder coated, compact cabinet for stationary operation
- Main control panel
- Pressure maintaining valve/Priority valve
- Pressure relief valves at all stages
- **Fully automatic condensate drain**
- **Final pressure switch with gauge with Auto-Shut-off**
- **Hour meter Analog**
- **Low oil shut down switch**
- **Cabinet High temperature shut down switch**
- **Interstage Pressure Gauges (3 pcs)**
- Final pressure gauge 400bar / 5800psi
- External oil level sight glass indicator with oil drain
- 1,7 Liter (59 oz.) SeaComAir compressor oil ISO VG150
- Breathing air purification system consisting of activated carbon and molecular sieve
- **Meets all international breathing air standards for CGA Grade "E" Air and DIN EN12021**
- Two (2) High Pressure Filling hoses with SCUBA INT, DIN200 or DIN300 with On/Off valve and bleed
- Spare parts list and owners manual
- One year warranty
- Noise: 82 dB (ISO3746)
- Weight: 160 Kg (355 lbs)
- Dimensions: L 35"(90) x D 24"(60) x H 33,5"(85 cm)

Specifications

- Construction: Continuous duty air cooled, three stage, three cylinder high pressure compressor, all stainless steel interstage and final stage coolers Mounted in a powder coated steel cabinet.
- Max Pressure: 220bar/3200psi or 340bar/5000psi
- Approx. Output: 315 l/min / 11 FAD
- Max R.P.M.: 1500
- Lubrication: Splash lubrication with oil thrower pin
- Oil Type: SeaComAir synthetic compressor oil ISO VG150
- Oil Capacity: 1,7 Liters (59 oz.)
- Drive motors: AC electric motors, 3 phase, 50 or 60 Hz
- Features: **Automatic condensate drain system with collector**
Final pressure switch with gauge and automatic shut-off
Final pressure safety relief valve
Hour meter
Low oil shut down switch
Cabinet High temperature shut down switch
Interstage Pressure Gauges (3 pcs)

Factory Options

- MP330: Compressor 340bar/5000psi pressure
- PS300/CFS: Pressure Adapter manually 340-200bar(5000/3000psi)
- PCSD200: Filter control system with LED indicator of filter cartridge saturation

*Based on charging 11 Liter / 80 Cu. Ft. Cylinder from 35 bar / 500 psi to 200 bar / 3000 psi

Type

Model	Description	Charging Rate*	Drive Motor
SCA265E43/CFSF3	Compressor 315 l/min	315 l/min/14 scfm/19 m ³ /h	5,5 kW Electric 230/400/440V 50-60Hz 3Ph



www.seacomair.com

SeaComAir

Grenzhub 5a • D - 83229 Aschau • Germany
 Tel. +49/(0)8057/904674 • Fax +49/(0)8057/904676
 e-mail: info@seacomair.com