


SEACOMAIR 265E43/75OSS Electric 340 bar/5000 psi



Two Filling Valve DIN200 or DIN300 with On/Off Valve and bleed

High pressure, breathing air compressor with *Open INOX Stainless Steel Frame* for Scuba, Fire Departments, Police, Military and Rescue units. Breathing air purification according to international standards. Designed for economy and mobility.

Standard Features

- **Charging rate* 315 l/min / 14 scfm @ 340bar/5000psi**
- **Fills an 11 Liter (80cu.ft.) cylinder in app. 5,5 min.***
- **Mounted on Stainless Steel Inox frame**
- **Large capacity moisture separators for hot and humid climates**
- **Breathing air purification system consisting of activated carbon and molecular sieve**
- **Meets or exceeds all international breathing air standards for CGA Grade "E" Air and DIN EN12021**
- Disposable purification cartridge is easy to replace, Intake filter
- Manual condensate drain
- **Priority/Back pressure maintaining valve**
- **Pressure safety relief valve on all stages**
- **Final safety pressure relief valve**
- Oil filled pressure gauge 0~400bar/5800psi
- 1,7 Liter SeaComAir synthetic compressor oil ISO VG150
- **Two (2) High Pressure Filling hoses with SCUBA INT, DIN200 or DIN300 with On/Off valve and bleed**
- Electric motor 400/440V 50 or 60Hz 3 phase with electrical control, ON/OFF Switch, and cabel
- Spare parts list and owners manual
- Available in a variety of factory options to fit any requirement
- Noise 82 dB (ISO3746)
- Weight: 125 kg (275 lbs)
- Dimensions L 39" (100) x D 20" (50) x H 28" (71 cm)
- One year warranty

Specifications

- Construction: Continuous duty air cooled, three stage, three cylinder high pressure compressor **all stainless steel interstage and final stage coolers.**
Mounted on a free standing, shock mounted, heavy duty Stainless Steel frame
- Max Pressure: 220bar/3200psi or 340bar/5000psi
 Approx. Output: 315 l/min/ 13 FAD
 Max. r.p.m.: 1550
 Lubrication: Splash lubrication with oil thrower pin
 Oil Capacity: 1,7 Liter (59 oz)
 Oil Type: SeaComAir synthetic compressor oil ISO VG150
 Drive motors AC electric motors, 3phase, 50 or 60 Hz **with electrical control, ON/OFF Switch and cabel**

Factory Options

- **MP330: Compressor 340bar/5000psi max. pressure**
- HMAE100: Hour meter Analog
- **PS300/100: Pressure Adapter 300-200bar (4300/3000psi)**
- WS200/2 Wheel Set (2 wheels)

*Based on charging 11 Liter / 80 Cu. Ft. Cylinder from 35 bar / 500 psi to 200 bar / 3000 psi

**32A 3P+E plug not supplied

Type

Model	Description	Charging Rate*	Drive Motor
SCA265E43/75OSS	Compressor 315 l/min - 14 scfm	315 l/min/14 scfm/19 m ³ /h	5,5kW Electric 400/440V/50-60Hz 3Ph



www.seacomair.com

SeaComAir

Grenzhub 5a • 83229 Aschau • Germany
 Tel. +49-8057-904674 • Fax +49-8057-904676
 e-mail: info@seacomair.com