SEACOMAIR 300 NITROX SILENT

Nitrox Low Pressure Generator Silent fully automatic



Meets all international breathing air standards for CGA Grade "D" Air

> ISO9001: 2009 Certified Factory



The most user-friendly and most cost effective Nitrox production system available today. SeaComAir LP Nitrox System with Semi-Permeable Membrane produce oxygen-rich air, Nitrox mixture 32 % to 36 % Oxygen.

Standard Features

- Low Pressure Silent Compressor cabinet for stationary operation Construction:
- Supply Low Pressue Nitrox 21% through 36% Oxygen
- Quick and easy to operate
- Safe, as there is never high partial pressure Oxygen involved
- Main control panel with Hour Meter
- High Pressure and Temperature Automatic Shut Off
- Automatic Condensate Drain
- Integrated Air Dryer for Long Filter life
- LP Filtration for Membrane
- Two Nitrox O2 Analyzers
- Operates on CGA Grade D Air
- Quiet Operation and Low maintenance
- One year warranty
- Noise level 70 dB (ISO3746)
- Weight 215 kg (660 lbs)
- Dimensions L 30" (76) x D 34" (86) x H 52" (132 cm)

Specifications

Construction: Rotary Screw Low Pressure Compressor

Nitrogen Permeable Membrane system

Mounted in a powder coated steel cabine

Mounted in a powder coated steel cabinet

Sound absorbing housing

Operating Pressure: 6 -10 bar / 90 - 145 psi

Air Volumen: 300 - 1000 l/min / 10,8 - 35 cfm
Oil Type: SeaComAir LP oil ISO VG146
Drive motor: AC electric motor 230/400/440 Volt.

3 phase 50Hz o.60Hz

Features: Final pressure gauge

Emergency shut-off,

Automatic Condensate Drain High Pressure Automatic Shut Off Temperature Automatic Shut Off

Type

JI					
	Model	Description	Capacity @ 10 bar*	Drive Motor	
	SCA300E43/EAN	Nitrox Low Pressure Generator	1000 l/min - 35 cfm	7.5 kW 230/400/440V/50 or 60Hz el. motor 3 phase	

*Low Pressure Screw Compressor Capacity at ambient input pressure

SeaComAir

Grenzhub 5a • 83229 Aschau • Germany Tel. +49/(0)8057/904674 • Fax +49/(0)8057/904676

e-mail: info@seacomair.com



SEACOMAIR 300 NITROX LP connection to HP Compressors

The Low Pressure Nitrox and High Pressure Compressor Packages will supply 32 %, 34 % or 36% Nitrox. This systems are most cost effective Nitrox production from 300 L/min - 10 cfm up to 550 L/min - 19 cfm.

SCA300E43/EAN Silent



SCA265E43/CFSF3 electric



Output Oxygen	Connect High Pressure Compressor	Electric Motor	Free Air Delivery
36% Nitrox EAN	SeaComAir 265 Compact Cabinet	5,5 kW 400/440V 50-60Hz 3Ph	300 L/min - 10 cfm

SCA300E43/EAN Silent



SCA400E43/HDF-OP electric



Output Oxygen	Connect High Pressure Compressor	Electric Motor	Free Air Delivery
34% Nitrox EAN	SeaComAir 400 Heavy Duty Cabinet	7,5 kW 400/440V 50-60Hz 3Ph	400 L/min - 14 cfm

SCA300E43/EAN Silent



SCA550E43/HDF-OP electric



Output Oxygen	Connect High Pressure Compressor	Electric Motor	Free Air Delivery
32% Nitrox EAN	SeaComAir 550 Heavy Duty Cabinet	9 kW 400/440V 50-60Hz 3Ph	550 L/min - 19 cfm

For more information about SeaComAir 300 Nitrox Silent Generator and HP Compressor Packages contact us at: info@seacomair.com



SeaComAir

Grenzhub 5a • 83229 Aschau • Germany Tel. +49/(0)8057/904674 • Fax +49/(0)8057/904676

e-mail: info@seacomair.com