

# SEACOMAIR FP3/2 Filling Panels



## Specifications FP3SSC INOX Filling Panel

- Filling panel with working pressure 4x300bar/4400psi
- Heavy duty Stainless Steel cabinet
- All stainless steel pipes
- Inlet fitting 300bar W7/16" UNF for high pressure air compressor
- One (1) 400bar/5800psi pressure gauge
- Four (4) 300bar/4400psi fittings W7/16" with On/Off lever valves
- Four (4) 300bar DIN300 Filling connection with HP Hose
- Safety relief valve
- Weight: 7,5 kg (16,5 lbs)
- Dimensions: L 63 (25") x D 16 (6.5") x H 20 cm (8")

## Specifications FP3/2SSC INOX Filling Panel

- Filling panel with working pressure 2x300bar/4400psi and 2x200bar/2900psi
- Heavy duty Stainless Steel cabinet
- All stainless steel pipes
- Inlet fitting 300bar W7/16" UNF for high pressure air compressor
- Two (2) 400bar/5800psi pressure gauges
- Two (2) 300bar/4400psi filling fittings W7/16" with On/Off lever valves
- Two (2) 200bar/2900psi filling fittings W7/16" with On/Off lever valves
- Pressure reducer for simultaneous filling
- Safety relief valve
- Weight: 8 kg (17.5 lbs)
- Dimensions: L 63 (25") x D 16 (6.5") x H 20 cm (8")

## Factory Options

- CO or Oxygen Analysers

## Type

Model	Description	System	Outlets
FP3/2SSC	Filling Panel 300bar/4400psi & 200bar/2900psi	Panel-System INOX	2x300 bar/4400 psi & 2x200 bar/2900 psi
FP3SSC	Filling Panel 300bar/4400psi	Panel-System INOX	4x300 bar/4400 psi



[www.seacomair.com](http://www.seacomair.com)

**SeaComAir**

Grenzhub 5a • D - 83229 Aschau  
 Tel. +49/(0)8057/904674 • Fax +49/(0)8057/904676  
 e-mail: [info@seacomair.com](mailto:info@seacomair.com)